

Application

Upholstery

Content

Top - 100% Silicone, Inherently Graffiti-Free®
*Middle - 100% Polyurethane (Polycarbonate Based)
*Patented, innovative silicone hybrid transfer prints

Backing

100% Polyester

Width

53/54"

Repeat

App. 33.5" H

General Characteristics

Abrasion : 200,000+ double rubs (Wyzenbeek)†
Hydrolysis Resistance : 15+ weeks
- ISO1419:1995, Method C, Tropical Test
Silicone does not support microbiological growth
Colorfastness to light (AATCC-16/200 hours)
Print Retention (ASTM D3389-10) Grade 5
Meets or Exceeds all ACT Heavy Duty Performance
Guidelines for Upholstery

Flammability

CA Bulletin 117-2013, UFAC/NFPA 260
IMO A652 (16) 8.2

Environmental


DMF Free, PVC/Phthalates Free, FR/Anti-Microbial Free
*Human/Nature Friendly Silicone Based
*Complies with REACH, Prop 65, HHI, CAL 01350

Maintenance*


W-Water Based Cleaners, Bleach Cleanable (4:1)

Warranty

Please refer to our Terms of Sales for warranty information.



Pepper



* While this product offers excellent protection against ink marks or difficult stains, full removal is not always guaranteed, if stains not addressed promptly.

† Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.